

KEMPEROL® 165 Fleece

Uses

- As reinforcement for **KEMPEROL®** waterproofing systems.
- For new construction and remedial projects

Features

- system tested and adapted to the specific purpose
- regulates the layer thickness
- suitable to every shape of the surface

CE-Marking

Component to 3	ETA 03/0025
	ETA 03/0026
	ETA 03/0043
	ETA 03/0044

Composition

Special fleece based on polyester.

Pack sizes

Rolls

Length in metres: 50

Width in cm: 105 / 70 / 52.5 / 35 / 26.25 / 21 / 10.5

Length in metres: 25

Width in cm: 26.25

Shelf Life

Keep away from dampness, store dry, flat and crease-free.

Properties

Form	solid
Colour	white
Weight [g/m ²]	approx. 165



Application

Approximately 2/3rd of the required **KEMPEROL®** resin should be applied to the primed substrate prior to embedding the **KEMPEROL® 165 Fleece**. All overlaps in the fleece should be saturated to ensure continuity of the system, and be a minimum of 50 mm.

When this has changed colour by rolling or brushing from above, the remaining 1/3rd of resin is applied to the surface and lightly rolled to remove excess material.

The interface with door and window elements etc., minimum recommended height 15 cm, should have a minimum 5 cm overlap. Connections to the surface waterproofing should be made with a minimum 10 cm overlap.

Disposal

Fleece EWC 04 02 21

General information

We guarantee the consistent high quality of our products.

KEMPER SYSTEM products must not be mixed with other manufacturers' products.

The technical information and application instructions contained herein reflect the current level of knowledge and experience with our products. In each case, the new edition supersedes the previous technical information and renders it invalid. It is therefore necessary that you always have to hand the current code of practice. When using our products, a detailed, object-related and qualified inspection is required in each individual case in order to determine whether the product and / or application technology in question meets the specific requirements and purposes. We are liable only for our products being free from faults - correct application of our products therefore falls entirely within your scope of liability and responsibility. Our products are sold exclusively on the basis of our conditions of sale and delivery.

Published: Vellmar, June 2008